

What is claimed is:

1. A diffraction device for periodically dividing an electromagnetic wave, the diffraction device comprising:
5 a diffraction grating;
an input medium contacting the diffraction grating; and
an output medium contacting the diffraction grating,
with at least either one of the input medium and output
medium comprising a photonic crystal having a periodic
10 characteristic in single direction, or the diffraction
grating comprising a photonic crystal, which periodically
divides electromagnetic waves to produce a phase difference
in a wave front with differences in optical propagation
distances between the divided electromagnetic waves.

15

2. The diffraction device according to claim 1,
wherein the photonic crystal satisfies the condition of

$$2 \leq | (\Delta\lambda / \lambda_0) / (\Delta\omega / \omega_0) |,$$

whereas λ_0 represents the wavelength of a propagating
20 wave when an electromagnetic wave having frequency ω_0
propagates in a specific direction in the photonic crystal,
and $\Delta\lambda$ represents the change of wavelength relative to an
electromagnetic wave having frequency $\Delta\omega + \omega_0$ when the
frequency ω_0 is changed by a slight amount.

25

3. The diffraction device according to claim 1,
wherein the photonic crystal includes a periodic direction
and said at least either one of the input medium and the
output medium comprising the photonic crystal, includes end
30 surfaces perpendicular to the periodic direction of the
photonic crystal as an input surface and an output surface,
the photonic crystal includes a photonic band gap and a
photonic band in the vicinity of the photonic band gap, and

the electromagnetic waves entering the input surface are propagated by the photonic band.

4. The diffraction device according to claim 1,
5 wherein the photonic crystal includes end surfaces from which the periodic characteristic is exposed as an input surface and an output surface, a photonic band structure having a line, which is either a Brillouin zone boundary line or a central line, and a photonic band, and electromagnetic
10 waves entering the input surface are propagated by one of:
the photonic band, which exists on the Brillouin zone boundary line of the photonic band structure or in the vicinity of the Brillouin zone boundary line; and
the photonic band, which exists on the central line of
15 the photonic band structure or in the vicinity of the central line.

5. The diffraction device according to claim 4,
wherein the photonic crystal includes an end surface
20 parallel in the periodic direction of the photonic crystal as an input surface and an output surface, the photonic crystal including a period, the diffraction device further comprising:
an input phase modulating unit for generating a phase
25 modulation wave having a period that is the same as or two times the period of the photonic crystal, wherein the input phase modulating unit is arranged contacting, near, or integrally with the input surface.

- 30 6. The diffraction device according to claim 5, wherein the phase modulating unit is a phase grating having a period that is the same as or two times the period of the photonic crystal.

7. The diffraction device according to claim 4, wherein the photonic crystal outputs wave, the diffraction device further comprising:

5 an output phase modulating unit for converting the light output from the photonic crystal to a plane wave, with the output phase modulating unit arranged contacting, near, or integrally with the output surface.

10 8. The diffraction device according to claim 4, wherein the photonic crystal has a periodic direction and an inclined input surface or inclined output surface that is inclined relative to the periodic direction of the photonic crystal, and inputs a plane wave to the inclined input
15 surface or outputs a plane wave from the inclined output surface.

9. The diffraction device according to claim 1, wherein the photonic crystal has an end surface, which
20 includes a reflective diffraction grating that comprises said diffraction grating, and when electromagnetic waves including plural frequency components are input to the photonic crystal, the reflective diffraction grating produces diffracted wave for each of the plural frequency
25 components of the electromagnetic wave in different directions.

10. The diffraction device according to claim 9, the diffraction device may be used with an electromagnetic wave
30 detector and the photonic crystal includes a periodic direction and the input medium and the output medium both comprise the photonic crystal and form a waveguide having an input surface and end surface parallel to the periodic

direction of the photonic crystal, with the reflective diffraction grating comprising a blazed reflective diffraction grating arranged in the end surface of the waveguide, and the diffraction device forming a
5 demultiplexer for outputting electromagnetic waves, which include plural frequency components input from the input surface of the waveguide, with the blazed reflective diffraction grating from the input surface as diffraction waves in different directions for each frequency component
10 to couple the electromagnetic waves with the electromagnetic wave detector or the waveguide.

11. The diffraction device according to claim 10, further comprising:

15 a lens element having a convex lens effect to input the electromagnetic waves including plural frequency components to the input surface of the waveguide as parallel light bundle, wherein electromagnetic waves output from the waveguide are collected by the lens element and coupled with
20 the electromagnetic wave detector when used therewith or the waveguide.

12. The diffraction device according to claim 10, wherein the input surface of the waveguide comprises a
25 convex lens-like input surface, with the electromagnetic waves including plural frequency components being input to the waveguide as a parallel light bundle produced by the convex lens-like input surface, and collected light bundle produced by the input surface of the convex lens-like
30 surface from the electromagnetic wave output from the photonic crystal in different directions for each frequency component coupled with the electromagnetic wave detector when used therewith or the waveguide.

13. The diffraction device according to claim 10,
wherein the blazed reflective diffraction grating has a
concave mirror-like diffraction grating surface and collects
5 electromagnetic waves separated into frequency components
with the concave mirror-like diffraction grating surface and
outputs the collected electromagnetic waves from the
waveguide.

10 14. The diffraction device according to claim 10,
wherein the waveguide is a slab waveguide.

15 15. The diffraction device according to claim 10,
wherein the photonic crystal includes a period, the
diffraction device further comprising:

an input phase modulating unit for generating a phase
modulation wave having a period that is the same as or two
times the period of the photonic crystal, wherein the input
phase modulating unit is arranged contacting, near, or
20 integrally with the input surface of the waveguide.

16. The diffraction device according to claim 15,
wherein the input phase modulating unit is a phase grating
having a period that is the same as or two times the period
25 of the photonic crystal.

17. The diffraction device according to claim 1,
further comprising:

an array waveguide diffraction grating including an
30 input slab waveguide connected to the input waveguide, an
output slab waveguide connected to output waveguide, and an
arrayed waveguide connected between the two slab waveguides
and generating an optical path length difference, with the

arrayed waveguide comprised of the photonic crystal as the diffraction grating that periodically divides electromagnetic waves and produces a phase difference in the wave fronts of the divided electromagnetic waves.

5

18. The diffraction device according to claim 17, wherein the arrayed waveguide includes a plurality of waveguides, each comprised of the photonic crystal, and adjacent waveguides have different lengths.

10

19. The diffraction device according to claim 17, wherein the arrayed waveguide includes a plurality of waveguides, each comprised of the photonic crystal with adjacent waveguides having the same length, and by changing
15 the period, material, or configuration of the photonic crystal comprising each of the waveguides, an optical path length difference is produced between adjacent waveguides.

20. The diffraction device according to claim 17,
20 wherein the input waveguide, the input slab waveguide, and the arrayed waveguide each have an input surface, the diffraction device further comprising:

an input phase modulating unit for generating a phase modulating wave having a period that is the same or two
25 times the period of the photonic crystal configuring the arrayed waveguide, with the phase modulating unit arranged contacting, near, or integrally with one of the input surface of the input waveguide, the input surface of the input slab waveguide, and the input surface of the arrayed
30 waveguide.

21. The diffraction device according to claim 17, wherein the output waveguide, the output slab waveguide, and

the arrayed waveguide each have an output surface, the diffraction device further comprising:

an output phase modulating unit for converting wave output from the arrayed waveguide to a plane wave, with the
5 output phase modulating unit arranged contacting, near, or integrally with one of the output surface of the output waveguide, the output surface of the output slab waveguide, and the output surface of the arrayed waveguide.

10 22. The diffraction device according to claim 17, the photonic crystal includes a period and the phase modulating unit is a phase grating having a period that is the same or two times the period of the photonic crystal configuring the arrayed waveguide.

15 23. The diffraction device according to claim 1, wherein the photonic crystal comprises a multilayer body in which dielectric bodies having different refractive indices are superimposed in periods that are about the same as the
20 wavelength of light.